

Walk-behind Trowels (Standard)

CT 36-5A

CT 36-6

CT 48-8A

CT 48-9

CT

High quality finishing plus triple protection

»» Designed and built with the most advanced technology, Wacker Neuson walk-behind trowels offer high quality concrete finishing plus added operator safety. The patented gearbox brake, patented gyroscopic safety sensor and patent-pending engine speed limiter provide triple protection for the operator. This unique system minimizes a runaway handle situation. ««



ADDITIONAL ADVANTAGES:

- **Patented dynamically balanced trowels** (when blades are turning) offer nearly effortless operation.
- **Optimum weight distribution** reduces the lateral force from the trowel for reduced operator fatigue.
- **Trowels feature a 30-degree blade pitch** for better concrete burnishing.
- **For maximum flexibility**, engine type, trowel diameter and handle type can be selected to meet individual preferences or job site conditions. (Handle sold separately.)
- **Guard ring features tubular framing** for easy cleaning and maintenance.



**WACKER
NEUSON**

Technical Data		CT 36-5A	CT 36-6	CT 48-8A	CT 48-9
Length x width x height (with solid handle)	in (mm)	79 x 37 x 41 (2007 x 940 x 1041)	79 x 37 x 41 (2005 x 940 x 1041)	84 x 48 x 41 (2160 x 1220 x 1041)	85 x 48 x 41 (2134 x 1220 x 1041)
Base model weight (without handle)	lb (kg)	183 (83)	183 (83)	234 (106)	227 (103)
Shipping size (l x w x h) (without handle)	in (mm)	40 x 40 x 29 (1016 x 1016 x 737)	40 x 40 x 29 (1040 x 1016 x 737)	50 x 44 x 42 (1260 x 1118 x 1067)	50 x 44 x 42 (1260 x 1118 x 1067)
Shipping weight (without handle)	lb (kg)	220 (110)	220 (110)	284 (130)	277 (126)
Trowel diameter	in (mm)	36 (915)	36 (915)	48 (1220)	48 (1220)
Number of blades		4	4	4	4
Speed range	rpm	60-125	60-125	60-125	60-125
Pitch range	degrees	0-30°	0-30°	0-30°	0-30°
Engine type		Honda GX160	air-cooled, 4-cycle, single-cylinder, gasoline engine WM 170		WM 270
Operating speed	rpm	3800	3800	3800	3800
Max. rated power at rated speed	hp (kW) rpm	4.8 (3.6) 3600	5.7 (4.3) 4000	7.1 (5.3) 3600	9 (6.6) 4000
Power rating specification		SAE J1349	SAE J1349	SAE J1349	SAE J1349
Piston displacement	in ³ (cm ³)	9.9 (163)	10.3 (169)	14.8 (242)	16.2 (265)
Fuel tank capacity	qt (l)	3.3 (3.1)	3.8 (3.6)	5.6 (5.3)	6.4 (6.1)
Fuel consumption	qt (l)/h	1.9 (1.8)	1.6 (1.5)	2.8 (2.7)	2.6 (2.5)

Standard Package

Walk-behind Trowels

CT 36-5A
CT 36-6
CT 48-8A
CT 48-9

includes combination blades, operator's manual and parts book.

Model Guide

CT = Concrete trowel (walk-behind)

36/48 = Trowel diameter in inches

5/6/8/9 = Engine class

A = Honda engine

Standard models feature Wacker Neuson WM engine.

Please refer to our Price List and Ordering Guide for complete accessory information.



Handle Guide

	Solid	Height Adjustable	Folding	Twist Pitch	Pro-Shift®	Weight lb (kg)
Adj-P		X			X	29 (13)
Fold-Adj-P		X	X		X	33 (15)
Fold-T			X	X		27 (12)
Fold-Adj-T		X	X	X		29 (13)
Adj-T		X		X		25 (11)
T	X			X		23 (10)

Specifications may change due to continuous product development. Users are advised to consult Wacker Neuson's Operator's Manual and website for specific information regarding the engine power rating. Actual power output may vary due to conditions of specific use.

