

6" CHANNEL EQUIPMENT TILT (T6)



Length: 16-24' Load Angle: 11°
 Deck Height: 21" Deck Width: 82"
 Couplers: Bumper Pull, Gooseneck, & Pintle

GVWR: 14,000-21,000 lbs
 Load Capacity: 10,580 lbs (20 ft Bumper Bull)
 Weight: 3,420 lbs (20 ft Bumper Pull)



HYDRAULIC PROPORTIONING VALVE



Hydraulic Cushioned Gravity Tilt
 Our gravity tilts use a hydraulic cylinder, reservoir, and proportioning valve to control the rate the trailer tilts.



Knife-Edge Tail
 Our 30" diamond plate knife-edge tail makes it super easy to load low clearance equipment like scissor lifts and fork lifts.



Low Load Angles
 The use of torsion axles and our unique frame design allow us to keep our deck heights low, giving us extremely low load angles.

21" DECK HEIGHT	14k BASE GVWR	2 5/16" ADJUSTABLE BULLDOG COUPLER	6" CHANNEL FRAME	3" CHANNEL CROSSMEMBERS	STEEL DIAMOND PLATE FENDERS	14 PLY 235/80/R16 RADIAL TIRES	DEXTER AXLE DEXTER EZ LUBE AXLES	TORSION SUSPENSION	82" WIDE DECK	16" CROSSMEMBER CENTERS	11° LOAD ANGLE	KNIFE-EDGE TAIL	TREATED PINE DECK	Bargman 7-WAY RV PLUG	LIFETIME LED LIGHTS	SHERRILL WILLIAMS POWDER COAT
--------------------	------------------	---------------------------------------	---------------------	----------------------------	-----------------------------	--------------------------------	----------------------------------	--------------------	------------------	----------------------------	-------------------	-----------------	-------------------	-----------------------	---------------------	-------------------------------